



## GREY NON-MARKING THERMOPLASTIC RUBBER WHEELS WITH POLYPROPYLENE CENTRE



### Description

Tyre: grey non-marking thermoplastic rubber.

Centre: polypropylene.

Hub with plain bore which houses the axle.

### Uses

Suitable for institutional trolleys, especially for catering. The grey non-marking thermoplastic rubber tyre makes them also suitable on delicate floorings. They can resist frequent washings and are therefore a good option in those environments where cleanliness must be guaranteed.

### Environments of use

Suitable for industrial and institutional environments, also in the presence of humidity. Not suitable in the presence of organic solvents, chlorinated substances, hydrocarbons and mineral oils. Not recommended in presence of strong organic and mineral acids.

WEAK ACIDS		WEAK BASES	
STRONG ACIDS		STRONG BASES	
WATER		HYDROCARBONS	
ALCOHOL		SOLVENTS	








*For information on the compatibility of the component wheel materials with specific aggressive chemical substances, see table at page 36.*

### Floors


It does not stain or damage fragile floors. Suitable for tiles and cement-resin. Not recommended on abrasive, unpaved floors or in the presence of processing residues.





















																
mm	mm	kg	COD.	mm	mm	daN										
40	18	0,01	381100	8	21	<b>30</b>										
50	20	0,02	381101	8	22	<b>40</b>										
60	24	0,04	381102	8	28	<b>60</b>										
75	24	0,05	381203	8	28	<b>70</b>										
80	24	0,07	381103	8	28	<b>70</b>										


**Institutional brackets**



- 1) Plate: electrolytically galvanised steel plate
  - 2) Fork: electrolytically galvanised steel plate
  - 3) Ball race ring: electrolytically galvanised steel plate
  - 4) Swivel actions: double ball ring with grease lubrication
  - 5) King pin: integrated with the plate and cold-rieveted
- Available with front locking brakes


																																	
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	mm	daN																		
40	18	0,09	384200	0,10	385200	0,12	388200	59	42x42	30x30	5	24	78	<b>30</b>																			
50	18	0,13	384201	0,14	385201	0,15	388201	66	55x55	40x40	6	24	78	<b>40</b>																			
60	24	0,22	384202	0,19	385202	0,26	388202	83	60x60	45x45	6	21	83	<b>60</b>																			
75	24	0,26	384303	0,22	385303	0,32	388303	101	60x60	45x45	6	25	91	<b>70</b>																			
80	24	0,28	384203	0,24	385203	0,33	388203	104	60x60	45x45	6	25	91	<b>70</b>																			

**Supporti per collettività**



- 1) Plate: electrolytically galvanised steel plate
  - 2) Fork: electrolytically galvanised steel plate
  - 3) Ball race ring: electrolytically galvanised steel plate
  - 4) Swivel actions: double ball ring with grease lubrication
  - 5) King pin: integrated with the plate and cold-riveted
- Available with front locking brakes

mm	mm	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	daN
40	18	0,08	383200	0,11	387200	59	35	10	24	78	<b>30</b>
50	18	0,10	383201	0,12	387201	66	35	10	24	78	<b>40</b>
60	24	0,19	383202	0,22	387202	83	41	12	21	83	<b>60</b>
75	24	0,23	383303	0,28	387303	101	41	12	25	91	<b>70</b>
80	24	0,24	383203	0,29	387203	104	41	12	25	91	<b>70</b>



- 1) Plate: electrolytically galvanised steel plate
  - 2) Fork: electrolytically galvanised steel plate
  - 3) Ball race ring: electrolytically galvanised steel plate
  - 4) Galvanised steel threaded stem
  - 5) Swivel actions: double ball ring with grease lubrication
- Available with front locking brakes

mm	mm	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN
40	18	0,09	386200	0,12	389200	59	35	M8	15	24	78	<b>30</b>
50	18	0,11	386201	0,14	389201	66	35	M8	15	24	78	<b>40</b>
60	24	0,22	386202	0,26	389202	83	41	M12	25	21	83	<b>60</b>
75	24	0,26	386303	0,32	389303	101	41	M12	25	25	91	<b>70</b>
80	24	0,28	386203	0,33	389203	104	41	M12	25	25	91	<b>70</b>

**Options available to order**



Various dimensions stems